



HydraGEN™

HG1R Series HG1R12NA

Technical Data

Diesel Engine Suitability	10 - 15 L	
Electrolyte Medium	Potassium Hydroxide	
Power Consumption	144 - 180 W	
Power Supply	12 VDC	
Power Draw	12 - 15 A	
Environment Temperature (min.)	-40°C	-40°F
Environment Temperature (max.)	50°C	122°F

Logistic Data

Dimensions (W x D x H)	510 x 248 x 610 mm 20 x 9.75 x 24"
Unit Weight	34.8 kg 76.8 lbs
Packaging Dimensions (H x B x T)	743 x 570 x 500 mm 29 x 22.5 x 20"
Weight Including Packaging	44.4 kg 97.8 lbs
Units per Pallet	6
Pallet Type/Size	1220 x 712 mm 48 x 30"
Harmonized Tariff Code	8543 3070

Exterior Details

Housing	Rugged Steel
Re-Filling Requirement	2 L Distilled Water 85 hr between refill
Distilled Water Refill Method	Remote fill tank with pump

Convenience

Communication	Cellular
Tracking	GPS
Other	HydraGEN™ App HydraLytica™ Driver notifications


Applications



Small Power Generators



Trucks



Construction Equipment



Farming Equipment