

HydraGEN™ HG2-15R



SUITABLE FOR

Normally Aspirated: 0-2L







FEATURES & BENEFITS

REDUCTION IN FUEL CONSUMPTION BY 6%-19.2%*

*6% certified by PIT Group, 19.2% from performance testing at UOIT

REDUCES GREENHOUSE GASES THAT ARE PRODUCED

REDUCES NO_X UP TO 46.1% | CO₂ UP TO 19.2% | CO UP TO 51% | THC UP TO 50.1%

REDUCES PARTICULATE MATTER BY OVER 65%

LONGER ENGINE LIFE

INCREASED POWER AND TORQUE

LONGER OIL LIFE +25%

REDUCTION OF DPF BY 33%

REDUCTION OF DEF USAGE BY 60%

TECHNICAL DATA

HG2 Engine: 1.51

Current: 10A at 12VDC

5A at 24VDC

120W Power Usage:

12VDC / 24VDC Electrical:

3.5L Water Reservoir: KOH: 1.25L

Communication: GPRS, Bluetooth, (GPS in future)

WEIGHT / DIMENSIONS

Unit size (h x w x d): 10" x 23" x 9"

Unit weight: 23 lbs Carton size: **TBD** Carton weight: TBD

26 x 59 x 23 cm Unit size:

Unit weight: 10.5 kg Carton size: TBD Carton weight: TBD Units per pallet: **TBD**

PRODUCT #: HG2-15R