

# **HydraGEN**<sup>™</sup>

# HG1R Series

#### **Technical Data**

Diesel Engine Suitability 10 - 15 L

Electrolyte Medium Potassium Hydroxide

Power Consumption 144 - 180 W

Power Supply 24 VDC

Power Draw 6 - 7.5 A

Environment Temperature (min.) -40°C -40°F

Environment Temperature (max.) 50°C 122°F

### **Logistic Data**

Dimensions (W x D x H) 510 x 248 x 610 mm

20 x 9.75 x 24"

Unit Weight 35.4 kg

78 lbs

Packaging Dimensions 743 x 570 x 500 mm

(H x B x T) 29 x 22.5 x 20"

44.9 kg 99 lbs

Units per Pallet 6

Weight Including Packaging

Pallet Type/Size 1220 x 712 mm

48 x 30"

Harmonized Tariff Code 8543 3070

#### **Exterior Details**

Housing Rugged Steel

Re-Filling Requirement 2 L Distilled Water 85 hr between refill

Distilled Water Refill Method Remote fill tank with

pump

## **Applications**







Construction Equipment



Trucks



Farming Equipment

#### Convenience

Communication Cellular

Tracking GPS

Other HydraGEN™ App

HydraLytica™

Driver notifications

dynaCERT Inc.

101-501 Alliance Ave. Toronto, ON M6N 2J1

Canada

+1 416 766 9691 info@dynacert.com