O HydraGEN[™]

HydraGEN[™] **HG2 Series** HG2R12NA

| Technical Data | | | Logistic Data | |
|--------------------------------|---------------------|-------|-------------------------------------|-------------------------------------|
| Diesel Engine Suitability | 1 - 8 L | | Dimensions (W x D x H) | 686 x 305 x 279 mm 27 x 12 x 11" |
| Electrolyte Medium | Potassium Hydroxide | | Unit Weight | 23.6 kg 52 lbs |
| Power Consumption | 144 - 180 W | | Packaging Dimensions (H x B x T) | 432 x 762 x 432 mm 17 x 30 x 17" |
| Power Supply | 12 VDC | | Weight Including Packaging | 34.9 kg 77 lbs |
| Power Draw | 12 - 15 A | | Units per Pallet | 6 |
| Environment Temperature (min.) | -40°C | -40°F | Pallet Type/Size | 1220 x 712 mm 48 x 30" |
| Environment Temperature (max.) | 50°C | 122°F | Harmonized Tariff Code | 8543 3070 |

Exterior Details

| Convenience | |
|-------------------------------|---|
| Distilled Water Refill Method | Remote fill tank with pump |
| Re-Filling Requirement | 1.5 L Distilled Water 85 hr between refill |
| Housing | Rugged Steel |

Communication

Tracking

Other

Cellular GPS

HydraGEN™ App

HydraLytica™

Driver notifications

dynaCERT Inc. 101-501 Alliance Ave. Toronto, ON M6N 2J1 Canada

+1 416 766 9691 info@dynacert.com

Applications





Delivery Vans



Refrigerated Trailers



Straight Trucks

Intercity/City Buses



School Buses



Pickup Trucks